

HOLORIB DECKING WITH  
CONCRETE SLAB

SPACE IN HOLORIB TO  
BE INFILLED WITH MINERAL  
WOOL OR INTUMESCENT FOAM

SEALANT

DRY PACKED WITH MINERAL  
WOOL IF A GAP IS PRESENT.

SEALANT

50 x 50 WFSL INTERNAL  
ANGLE RIVETED TO PANELS  
& HILTI FIXED TO SLAB.

PIR / MINERAL WOOL  
INSULATED WALL PANEL.

STEEL BASE CHANNEL, TO  
MATCH WALL PANEL FINISH,  
FIXED TO FLOOR SLAB USING  
HAMMER HIT. FIXINGS.  
CHANNEL SUITABLY SEALED &  
RIVETED TO PANELS.

MASTIC / SILICONE SEAL.

WATER RESISTANT  
SEALS.

INTUMESCENT SEALS.

**GLOBAL  
INSULATION**

SPECIALIST INSULATION TECHNICIANS  
TO THE WORLDWIDE CATERING, FOOD  
PROCESSING & COLDSTORAGE INDUSTRIES

UNIT 5a, SEVERNBRIDGE INDUSTRIAL ESTATE  
SYMONDSCLIFFE WAY, PORTSKEWETT,  
CALDICOT, MONMOUTHSHIRE, NP26 5PW

TEL: 00 44 1633 882048 ;  
FAX : 00 44 1633 882034  
E-MAIL : MRGIL42070@aol.com

TITLE;  
TYPICAL DETAIL; FIRE PANELS;  
TYPICAL SECTION THROUGH  
PARTITION WALL.

DRG. No; TDFR ~ 11